




Devices thru Material Innovation

NEC/TOKIN

Vol.
03

[DC Line Filter]




DC LINE FILTER

Contents


Classification of NEC TOKIN's EMI Suppression parts.	3
DIP type	
Common Mode Power Line	
SH Series	8
SHO Series	10
SBT-03 W Series	11
Common Mode Signal Line	
SBT-01 W Series	12
Toroidal Cores with Wound cables	13
DIP Noise Filters D-03C, 03C1, 05N1, 07C1, 08C2, 08C2A	14
DIP Noise Filters D-16C, 20C, 22C	16
DIP Noise Filters D-37C, 40C-47C	17
DIP Noise Filters D-55C, 58C	19
Common Mode (For Telephone Sets)	
Noise Filters for Telephone Sets LFT, HFT, SZ-03	20
Noise Filters for Telephone Sets ST-101, 201, 202, 202S	21
Noise Filters for Telephone Sets ST-101A, 201A, 202A	22
Noise Filters for Telephone Sets ST-110AV, 110AH, 110BV, 110BH	23
Noise Filters for Telephone Sets ST-101F2, 101F4	24
Noise Filters for Telephone Sets ST-104A4, 204A series	25
Normal Mode	
SBT Series	26
SNT Series	27
EMC Filters	
Distributed Constant Filters EK 30, 31, 32	28
Distributed Constant Filters EK 33	30
Feedthrough Capacitor Filters (EG Series)	31
EJ Series	32
DFD Series	33
Tape and Reel Dimensions	34
SMD type	
Common Mode Power Line	
SBS-9080 Series	36
SBP Series	37
DCM Series	38
Common Mode Signal Line	
EMC Chip Filters (M-500CT/M-600T Series)	40
SCM Series	42
Precautions	44
Tape and Reel Dimensions	45

Classification of NEC TOKIN's EMI suppression parts


NEC/TOKIN




(Continued)




(Continued)



(Continued)



(Continued)





SH Series





Model	Rated voltage DC (V)	Rated current (A)	Inductance (μ H) min.	DC resistance (m Ω /line) max.	Operating temperature range (°C)	Shape and dimensions
SH-101	150	3.0	0.35	16	-25 to +80	Fig. 1
SH-102	150	3.0	1.5	26	-25 to +80	
SH-201	150	3.0	0.5	16	-25 to +80	
SH-202	150	3.0	1.5	20	-25 to +80	
SH-301	150	3.0	3.2	22	-25 to +80	
SH-302	150	3.0	7.5	26	-25 to +80	
SH-211	150	3.0	0.5	18	-25 to +80	
SH-212	150	3.0	1.5	23	-25 to +80	
SH-311	150	3.0	3.2	25	-25 to +80	
SH-312	150	3.0	7.5	30	-25 to +80	
SH-121	50	3.0	0.35	11	-25 to +80	
SH-122	50	3.0	1.5	20	-25 to +80	
SH-221	50	3.0	0.5	11	-25 to +80	
SH-222	50	3.0	1.5	14	-25 to +80	
SH-321	50	3.0	3.5	14	-25 to +80	
SH-322	50	3.0	7.5	20	-25 to +80	Fig. 4
SH-132	50	2.4	2.6	51	-25 to +60	
SH-432	50	2.4	30.0	51	-25 to +60	
for 3 lines SH-S132	50	1.0	1.7	81	-25 to +80	Fig. 5



Shape and Dimensions/Circuit Diagram





●Fig. 2





●Fig. 3



●Fig. 4







●Fig. 5



[mm]

Impedance vs. Frequency




SHO Series




Model	Rated voltage DC (V)	Rated current (A)	Inductance (μ H) min.	DC resistance (m Ω /line) max.	Operating temperature range ($^{\circ}$ C)
SHO-101	50	4.0	2.0	15.5	-25 to +70
SHO-102	50	4.0	0.6	10.0	-25 to +70
SHO-201	50	4.0	5.0	15.5	-25 to +70
SHO-202	50	4.0	1.6	10.0	-25 to +70
SHO-301	50	4.0	12.0	15.5	-25 to +70
SHO-302	50	4.0	3.9	10.0	-25 to +70


Shape and Dimensions



Circuit Diagram



Impedance vs. Frequency



SBT-03W Series




Model	Rated voltage DC (V)	Rated current (A)	Inductance (100kHz, 1mA) (μ H) min.	DC resistance (m Ω) max.	Operating temperature range (°C)	Wire size (mm \varnothing)	Packaging
SBT-0308W	50	3.0	6.75	20	-25 to +85	0.4	
SBT-0310W	50	2.5	7.7	30	-25 to +80	0.35	
SBT-0315W	50	2.0	11.9	45	-25 to +75	0.3	Bulk (100 pcs.)

• Withstanding voltage: 200VDC (one minute, between lines)


• Insulation resistance: more than 10M Ω (100VDC, between lines)

Shape and Dimensions




[mm]

Circuit Diagram



[mm]

Impedance vs. Frequency



SBT-01W Series




Model	Rated voltage DC (V)	Rated current (mA)	Inductance (1kHz, 70mA) (μ H)	DC resistance (m Ω) max.	Operating temperature range (°C)	Packaging
SBT-0115W	50	500	≥ 5	30	-25 to +70	
SBT-0140W	50	500	$40 \pm 35\%$	40	-25 to +70	
SBT-0160W	50	500	$60 \pm 35\%$	45	-25 to +70	
SBT-0180W	50	500	$80 \pm 35\%$	55	-25 to +70	Bulk (100pcs.)

• Withstanding voltage: 200VDC (one minute, between lines)


• Insulation resistance: more than 10M Ω (100VDC, between lines)

Shape and Dimensions




[mm]

Circuit Diagram



[mm]

Impedance vs. Frequency



Troidal Cores with Wound Cables




Model	Core	Dimensions (mm)				No. of turns	Wire	Winding status	Frequency range (MHz)
		A	B	C	D				
ESD-H-12E	ESD-R-12C	16	20	5	25	7	UL1007 AWG26 ($\varnothing 0.4$)	Bi-filar winding	Up to 300
ESD-H-12M	ESD-R-12A	15	18.5	5	15	9	Teflon wire ($\varnothing 0.4$)	Bi-filar winding	Up to 100
ESD-H-14U	ESD-R-14A	17.5	7	5	15	10	UL1609 AWG26 ($\varnothing 0.4$)	Bi-filar winding	Up to 100
ESD-H-14NU	ESD-R-14C2	17.5	7	5	15	10	UL1609 AWG26 ($\varnothing 0.4$)	Bi-filar winding	Up to 300


• Recommended soldering conditions: $350 \pm 10^\circ\text{C}$, 2 to 3 sec.

Shape and Dimensions




●ESD-H Series



Circuit Diagram




Impedance vs. Frequency



DIP Noise Filters

D-03C, 03C1, 05N1, 07C1, 08C2, 08C2A




Model	Circuit diagram	Number of terminals/Circuits	Rated voltage DC (V)	Rated current DC (mA/Line)	DC resistance (mΩ/Line) max.	Operating temperature range (°C)
D-03C		4 cores			150	75
D-03C1		4 cores	50	100	150	-20 to +70
D-05N1		8 cores	50	100	10	-20 to +70
D-07C1		1 core	50	300	100	-20 to +70
D-08C2		1 core	50	2300	25	-20 to +70
D-08C2A		1 core	50	500	70	-20 to +70

• Withstanding voltage: 200VDC (one minute, between lines)


• Insulation resistance: more than 10MΩ (100VDC, between lines)

Shape and Dimensions


●D-03C, 03C1




●D-05N1




●D-07C1




●D-08C2



●D-08C2A




[mm]

Impedance vs. Frequency

DIP Noise Filters

D-16C, 20C, 22C




Model	Circuit diagram	Number of terminals/ Circuits	Rated voltage DC (V)	Rated current DC (mA/Line)	DC resistance (mΩ/Line) max.	Operating temperature range (°C)	
D-16C		1 core	8P/4 circuits Common mode	50	100	50	-20 to +70
D-20C		1 core	16P/8 circuits Common mode	50	500	40	-20 to +70
D-22C		1 core	6P/3 circuits Common mode	50	1500	40	-20 to +70

• Withstanding voltage: 200VDC (one minute, between lines)


• Insulation resistance: more than 10MΩ (100VDC, between lines)

Shape and Dimensions


●D-16C



●D-20C




●D-22C




[mm]

Impedance vs. Frequency



DIP Noise Filters

D-37C, 40C, 42C, 45C, 47C






Model	Circuit diagram	Number of terminals/ Circuits	Rated voltage DC (V)	Rated current DC (mA/Line)	DC resistance (mΩ/Line) max.	Operating temperature range (°C)	
D-37C		1 core	20P/10 circuits Common mode	50	300	200	-20 to +70
D-40C		1 core	6P/ 3 circuits Common mode	50	300	200	-20 to +70
D-42C		1 core	10P/ 5 circuits Common mode	50	300	200	-20 to +70
D-45C		1 core	16P/ 8 circuits Common mode	50	300	150	-20 to +70
D-47C		1 core	20P/ 10 circuits Common mode	50	300	200	-20 to +70

• Withstanding voltage: 200VDC (one minute, between lines)





• Insulation resistance: more than 10MΩ(100VDC, between lines)

Shape and Dimensions



Model	Number of Circuits	ℓ	L
D-40C	3	5.08	12.7 max.
D-42C	5	10.16	18 max.
D-45C	8	17.78	25 max.
D-47C	10	22.86	28 max.

[mm]

Impedance vs. Frequency

DIP Noise Filters

D-55C, 58C




Model	Circuit diagram	Number of terminal/ Circuits	Rated voltage DC (V)	Rated current DC (mA/Line)	DC resistance (mΩ/Line) max.	Operating temperature range (°C)	
D-55C		1 core	10P/5 circuits Common mode	50	300	200	-20 to +70
D-58C		1 core	16P/8 circuits Common mode	50	300	200	-20 to +70


• Withstanding voltage: 200VDC (one minute, between lines)

• Insulation resistance: more than 10MΩ (100VDC, between lines)

Shape and Dimensions



Impedance vs. Frequency



EMI/EMC Filters for Telephone Sets LFT, HFT, SZ-03




Model	Frequency range (MHz)	Impedance or attenuation (kΩ) min.	Rated voltage DC (V)	Rated current (mA)	DC resistance (Ω/line) max.	Operating temperature range (°C)	Remarks
LFT	0.5 to 7	27 (15 dB) (at 0.5 MHz)	50	100	10	-20 to +75	AM band
SZ-03	0.5 to 7	27 (at 0.5 MHz)	50	100	10	-20 to +75	AM band
HFT	7 to 40	2.6 (15 dB) (at 7MHz)	50	100	0.2	-20 to +75	FM band


• Withstanding voltage: 500VDC (one minute, between lines) • Insulation resistance: more than 10MΩ (250VDC, between lines)

Shape and Dimensions/Circuit Diagram


●LFT



●HFT




●SZ-03




[mm]

Installation Examples




Design Examples


① Installation at rosette or circuit input/output



② Insertion in Driver/ Receive circuit in telephone



Impedance vs. Frequency



EMI/EMC Filters for Telephone Sets

ST-101, 201, 202, 202S




Model	Frequency range (MHz)	Impedance (kΩ) min.	Rated voltage DC (V)	Rated current (mA)	DC resistance (mΩ/Line) max.	Operating temperature range (°C)	Remarks
ST-101	0.5 to 7	3 (at 0.5 MHz)	50	200	180	-20 to +75	AM band
ST-201	7 to 40	1.5 (at 7 MHz)	50	200	100	-20 to +75	FM band
ST-202	7 to 100	0.6 (at 100 MHz)	50	1000	40	-20 to +75	FM band
ST-202S	7 to 100	0.6 (at 100 MHz)	50	1000	35	-20 to +75	FM band


- Withstanding voltage: 500VDC (one minute, between lines)
- Insulation resistance: more than 10MΩ (250VDC, between lines)
- Recommended soldering conditions: 350±10°C, 2 to 3 sec.

Shape and Dimensions/Circuit Diagram



●ST-101, 201



●ST-202




●ST-202S




[mm]

Installation Examples




Design Examples


① Installation at rosette or circuit input/output



② Insertion in Driver/ Receive circuit in telephone




Impedance vs. Frequency



EMI/EMC Filters for Telephone Sets

ST-101A, 201A, 202A




Model	Frequency range (MHz)	Impedance (kΩ) min.	Rated voltage DC (V)	Rated current (mA)	DC resistance (mΩ/Line) max.	Operating temperature range (°C)	Remarks
ST-101A	0.5 to 7	3 (at 0.5 MHz)	50	200	250	-20 to +65	AM band
ST-201A	7 to 40	1.5 (at 7 MHz)	50	200	150	-20 to +65	FM band
ST-202A	7 to 100	0.6 (at 100 MHz)	50	1000	50	-20 to +65	FM band


• Withstanding voltage: 500VDC (one minute, between lines)

• Insulation resistance: more than 10MΩ (100VDC, between lines)

Shape and Dimensions/Circuit Diagram




Installation Examples




Design Examples


① Installation at rosette or circuit input/output



② Insertion in Driver/ Receive circuit in telephone



Impedance vs. Frequency



EMI/EMC Filters for Telephone Sets

ST-110AV, 110AH, 110BV, 110BH





Model	Frequency range (MHz)	Impedance (kΩ) min.	Rated voltage DC (V)	Rated current (mA)	DC resistance (mΩ/Line) max.	Operating temperature range (°C)	Remarks
ST-110AV	0.5 to 7	27 (at 0.5 MHz)	50	300	3	-20 to +75	AM band
ST-110AH	0.5 to 7	27 (at 0.5 MHz)	50	300	3	-20 to +75	AM band
ST-110BV	0.5 to 7	150 (Resonant)	50	150	7.5	-20 to +75	AM band
ST-110BH	0.5 to 7	150 (Resonant)	50	150	7.5	-20 to +75	AM band

• Withstanding voltage: 500VDC (one minute, between lines)



• Insulation resistance: more than 10MΩ(250VDC,between lines)

Shape and Dimensions/Circuit Diagram

●ST-110AV, ST-110BV




●ST-110AH, ST-110BH




[mm]

Installation Examples




Design Examples


① Installation at rosette or circuit input/output



② Insertion in Driver/ Receive circuit in telephone



Impedance vs. Frequency



EMI/EMC Filters for Telephone Sets ST-101F2, 101F4




Model	Frequency range (MHz)	Impedance (kΩ) min.	Rated voltage DC (V)	Rated current (mA)	DC resistance (Ω/Line) max.	Operating temperature range (°C)	Remarks
ST-101F2	0.5 to 7	40 (at 600 kHz)	50	200	2.7	-20 to +75	AM band
ST-101F4	0.5 to 7	60 (at 600 kHz)	50	200	3.5	-20 to +75	AM band

• Withstanding voltage: 500VDC (one minute, between lines)


• Insulation resistance: more than 10MΩ (250VDC between lines)

Shape and Dimensions/Circuit Diagram




[mm]

Installation Examples




Design Examples


① Installation at rosette or circuit input/output



② Insertion in Driver/ Receive circuit in telephone



Impedance vs. Frequency



EMI/EMC Filters for Telephone Sets ST-104A4, 204A Series




Model	Frequency range (MHz)	Impedance (kΩ) min.	Rated voltage DC (V)	Rated current (mA)	DC resistance (Ω/Line) max.	Operating temperature range (°C)	Remarks
ST-104A4	0.5 to 7	3.0 (at 0.5 MHz)	50	500	0.36	-20 to +75	AM band
ST-204A1	7 to 100	0.25 (at 10 MHz)	50	500	0.10	-20 to +75	FM band
ST-204A3	7 to 40	1.0 (at 7 MHz)	50	500	0.17	-20 to +75	FM band
ST-204A4	7 to 40	0.6 (at 7 MHz) REF	50	500	0.12	-20 to +75	FM band


• Withstanding voltage: 500VDC (one minute, between lines)

• Insulation resistance: more than 10MΩ (250VDC, between lines)

Shape and Dimensions/Circuit Diagram




Installation Examples




Design Examples


① Installation at rosette or circuit input/output



② Insertion in Driver/ Receive circuit in telephone



Impedance vs. Frequency



SBT Series




- Tape and Reel Dimensions (see page 34)

Model	Rated voltage DC (V)	Rated current (mA)	Inductance (1kHz, 70mA) (μ H)	DC resistance (m Ω) max.	Operating temperature range (°C)	Packaging
SBT-0208□	50	500	8±50%	20	-25 to +70	
SBT-0210□	50	500	10±50%	20	-25 to +70	
SBT-0240□	50	500	40±35%	34	-25 to +70	
SBT-0260□	50	500	60±35%	50	-25 to +70	Bulk (100pcs.)

- Taping (2000 pcs./ reel x 6), Flat taping (1000pcs./ box x 10)


Shape and Dimensions

●SBT-02□□



[mm]

Impedance vs. Frequency



SNT Series




- Tape and Reel Dimensions (see page 34)

Model	Rated current*	Inductance (μ H) min.	DC resistance (m Ω) max.	Operating temperature range (°C)	Packaging
SNT-S10□□	3.0	1.5	25	-20 to +60	
SNT-S20□□	1.5	6	35	-20 to +60	
SNT-S30□□	0.5	13	95	-20 to +60	
SNT-D10□□	3.0	2.5	25	-20 to +60	
SNT-D20□□	1.5	10	45	-20 to +60	Bulk (100 pcs.)
SNT-D30□□	0.5	20	98	-20 to +60	

*The rated current is for the wire and it is different from the inductance guaranteeing values.


- □ Taping (1000 pcs./ reel) • □ Flat taping (SNT-S type: 1000 pcs./ reel), (SNT-D type: 500 pcs./ reel)

Shape and Dimensions





Design Example

- For noise suppression in the secondary low-voltage power supply circuit



Impedance vs. Frequency



Distributed Constant Filters

EK 30, 31, 32




- Tape and Reel Dimensions (see page 34)

	Model	Rated voltage DC (V)	Rated current DC (mA)	DC resistance (mΩ) max.	Dielectric breakdown voltage DC (V)	Insulation resistance (MΩ) min.	Operating temperature range (°C)
Low Frequency Type 30	EK30-1103	50	500	105	125	2×10^4	-25 to +85
	EK31-050M	50	500	60	125	2×10^4	-25 to +85
	EK31-020M	50	500	60	125	2×10^4	-25 to +85
Low Frequency Type 31	EK31-010M	50	500	60	125	2×10^4	-25 to +85
	EK31-008M	50	500	60	125	2×10^4	-25 to +85
	EK31-004M	50	500	70	125	2×10^4	-25 to +85
	EK31-002M	50	500	110	125	2×10^4	-25 to +85
	EK31-001M	50	500	150	125	2×10^4	-25 to +85
	EK32-200M	50	500	60	125	2×10^4	-25 to +85
Low Frequency Type 32	EK32-150M	50	500	60	125	2×10^4	-25 to +85
	EK32-100M	50	500	60	125	2×10^4	-25 to +85
	EK32-080M	50	500	60	125	2×10^4	-25 to +85

- The operating temp. range includes the self-temp. rise.


Shape and Dimensions



Model	W max.	H max.	T max.	P ₁ ^{+0.4} _{-0.2}	P ₂ ^{+0.4} _{-0.2}	J max.	d ^{±0.05}	Per Box
30 type	8.0	12.0	5.0	2.5	2.5	1.0	0.5	1000
31 type	7.0	5.0	2.5	2.5	2.5	1.0	0.5	2000
32 type	7.5	9.5	3.5	2.5	2.5	1.0	0.5	1500

[mm]

Circuit Diagram



Numbering System

EK **①** **②** - **③** **M** **④**

(1) Series



(2) Type

(3) Nominal cut-off frequency



(4) TF : Taping (EK 30 type: 1000 pcs./box, EK 31 type: 2000pcs./box, EK 32 type: 1500 pcs./box)

Attenuation Characteristics

●EK 30, EK 31 Type



●EK 32 Type



Distributed Constant Filters

EK 33




• Tape and Reel Dimensions (see page 35)

Model	Rated voltage DC (V)	Rated current DC (mA)	Dielectric breakdown voltage DC (V)	Insulation resistance (MΩ) min.	DC resistance (MΩ) max.	Capacitance (Reference) C (pF)	Operating temperature range (°C)	Attenuation level (dB) min.
EK33-250NB	50	500	125	3×10^4	85	25	-25 to +85	10 (at 260 to 700 MHz)
EK33-500NB	50	500	125	3×10^4	140	50	-25 to +85	10 (at 120 to 800 MHz)
EK33-131NB	50	500	125	3×10^4	200	130	-25 to +85	10 (at 60 to 800 MHz)

• The operating temperature range includes self-temperature rise.


Shape and Dimensions



Model	W max.	H max.	T max.	P ₁ +0.4 -0.2	P ₂ +0.4 -0.2	J max.	d ±0.05	Per Box
EK33-250NB	8.3	10.0	4.5	2.5	2.5	2.0	0.5	1000
EK33-500NB	8.3	10.0	4.5	2.5	2.5	2.0	0.5	1000
EK33-131NB	9.0	7.5	4.5	3.5	2.5	2.0	0.5	1000

[mm]

Circuit Diagram




Numbering System

EK - ○○ - ○○○ - ○○
 ① ② ③ ④

(1) Series
 (2) Type
 (3) Capacitance
 (4) TF : Flat taping (1000 pcs./box)

Attenuation Characteristics



Feedthrough Capacitor Filters EG Series




Model	Rated voltage DC (V)	Rated current (A) max.	Operating temperature range (°C)	Storage temperature range (°C)
EG-□-□□□□	50	5	-25 to +85	-40 to +100


• Withstanding voltage: 125VDC • Insulation resistance: 1000MΩ

Shape and Dimensions

●EG-8 type




●EEG-4 type



[mm]

Circuit Diagram




Numbering System

EG-□-□□□□□

① 3:3 line, 4:4 line, 8:8 line
② 470S : 47pF, 101S : 100pF, 271S : 270pF, 471P : 470pF, 102P : 1,000pF

Attenuation Characteristics




EJ Series




Model	Rated voltage DC (V)	Rated current (A) max.	Operating temperature range (°C)	Storage temperature range (°C)
EJ-2-332P	50	10	-25 to +85	-40 to +100

- Withstanding voltage: 300VDC, 1 to 5 seconds, between lines (INPUT-OUTPUT-GROUND)
- Insulation resistance: more than 1000MΩ (50VDC, one minute)


Shape and Dimensions




Circuit Diagram



Attenuation Characteristics




DFD Series



Model	Rated voltage DC (V)	Rated current DC (A)	DC resistance (mΩ) max.	Operating temperature range (°C)
DFD-104P	50	2.0	100	-25 to +85
DFD-104S	50	2.0	100	-25 to +85


• Withstanding voltage: 125VDC, 5 sec. between terminal 1 and 2 • Insulation resistance: more than 500MΩ (100VDC, one minute)

Shape and Dimensions/Circuit Diagram



[mm]


Attenuation Characteristics



Tape and Reel Dimensions


SBT Series

Tape and Reel Dimensions




SNT Series

Tape and Reel Dimensions



Distributed Constant Filters EK 30, 31, 32


Tape and Reel Dimensions



Model	W max.	H max.	T max.	P ₁ +0.4, -0.2	P ₂ +0.4, -0.2	J max.	d ±0.05	Per Box
30 type	8.0	12.0	5.0	2.5	2.5	1.0	0.5	1000
31 type	7.0	5.0	2.5	2.5	2.5	1.0	0.5	2000
32 type	7.5	9.5	3.5	2.5	2.5	1.0	0.5	1500

Distributed Constant Filters EK33

Tape and Reel Dimensions



Model	W max.	H max.	T max.	P ₁ +0.4, -0.2	P ₂ +0.4, -0.2	J max.	d ±0.05	Per Box
EK33-250NB	8.3	10.0	4.5	2.5	2.5	2.0	0.5	1000
EK33-500NB	8.3	10.0	4.5	2.5	2.5	2.0	0.5	1000
EK33-131NB	9.0	7.5	4.5	3.5	2.5	2.0	0.5	1000

SBS-9080 Series




- Tape and Reel Dimensions (see page 45)
- Precautions (see page 44)


Model	Rated voltage DC (V)	Rated current DC (A)	Impedance (at 180MHz) (Ω) typ.	DC resistance (mΩ/line) max.	Operating temperature range (°C)
SBS9080-509T	50	5.0	1200	15	-25 to +50

- Withstanding voltage: 125V DC for one minute between lines
- Insulation resistance: More than 10MΩ (100V DC, between lines)


Shape and Dimensions




Circuit Diagram



Recommended Land Pattern



Impedance vs. Frequency



SBP Series






- Tape and Reel Dimensions (see page 45)
- Precautions (see page 44)

Model	Rated voltage DC (V)	Rated current DC (A)	Impedance (at 100MHz) (Ω) min.	DC resistance (mΩ/line) max.	Operating temperature range (°C)
SBP-5001T	50	5.0	500	7	-25 to +70


- Withstanding voltage: 200V DC for one minute between lines
- Insulation resistance: More than 10MΩ (100V DC, between lines)

Shape and Dimensions




[mm]

Circuit Diagram




Recommended Land Pattern




[mm]

Impedance vs. Frequency



DCM Series



• Tape and Reel Dimensions (see page 47) • Precautions (see page 44)

Model	Rated voltage (V)	Rated current (A)	L(μH) min	Rdc(mΩ) max	Type
DCM5-01	50	0.2	2540	3180	EE5
DCM5-02	50	0.5	520	510	EE5
DCM5-03	50	1.0	210	180	EE5
DCM5-04	50	2.0	30	30	EE5
DCM11-01	50	0.8	1350	240	ED11.6/5
DCM11-02	50	1.3	630	105	ED11.6/5


●Inductance measurement condition : f = 10KHZ 0.1V *●Insulation resistance : more than 100MΩ(DC250V, 1min, between lines) ●Operating temperature range(°C) : -20 to 110 (includes the selftemp.rise.)

Look : By number-of-turns adjustment, to products other than the above-mentioned characteristic is also possible, please consult.


●Common mode winding with section bobbin. *●Withstanding voltase : 250V DC for one minute between lines.

Shape and Dimensions

●DCM5 Series




●DCM11 Series




Recommended Land Pattern

●DCM5 Series




●DCM11 Series




Circuit Diagram

●DCM5 Series









●DCM11 Series




Impedance vs. Frequency

— Common-mode
- - - Normal-mode



EMC Chip Filters M-500CT/M-600T Series



• Tape and Reel Dimensions (see page 45-47) • Precautions (see page 44)

M-500CT Series

Model	Rated voltage DC (V)	Rated current DC (A)	Impedance (Ω) min.	DC resistance (m Ω) max.	Operating temperature range (°C)
M-521CT	50	1.0	700 (at 10 MHz)	100	-25 to +85
M-522CT	50	1.0	200 (at 20 MHz)	100	-25 to +85
M-523CT	50	1.5	200 (at 20 MHz)	65	-25 to +85
M-532CT	50	0.5	450 (at 100 MHz)	90	-25 to +85
M-538CT	50	0.1	800 (at 100 MHz)	220	-25 to +70
M-542CT	50	0.5	200 (at 10 MHz)	120	-20 to +75


M-600T Series

Model	Rated voltage DC (V)	Rated current DC (A)	Impedance (Ω) min.	DC resistance (m Ω) max.	Operating temperature range (°C)
M-608T	50	0.1	300 (at 100 MHz)	80	-20 to +80
M-614T	50	0.1	1000 (at 50 MHz)	120	-20 to +80
M-620T	50	0.1	1000 (at 30 MHz)	160	-20 to +80


• Insulation resistance: more than 10M Ω (100V DC, between lines)

Shape and Dimensions


●M-521CT, M-522CT, M-523CT




●M-532CT, M-538CT



●M-542CT




●M-608T, M-614T, M-620T




[mm]

Circuit Diagram


●M-521CT, M-522CT, M-523CT




●M-532CT, M-538CT



●M-542CT




●M-608T, M-614T, M-620T




Recommended Land Pattern


●M-521CT, M-522CT, M-523CT




●M-538CT





●M-542CT



●M-608T, M-614T, M-620T



[mm]

Impedance vs. Frequency**M-500CT Series****M-600T Series**

SCM Series



- Tape and Reel Dimensions (see page 47)
- Precautions (see page 44)


Model	Rated voltage (V)	Rated current (A)	L (μ H) min	Rdc (m Ω) max
SCM5-01	50	0.2	2540	3180
SCM5-02	50	0.5	520	510
SCM5-03	50	1.0	210	180
SCM5-04	50	2.0	30	30

● Inductance measurement condition : f = 10KHZ 0.1V * ● Insulation resistance : more than 100M Ω (DC100V, 1min, between lines) ● Operating temperature range(°C) : -20 to 110 (includes the selftemp.rise)


Look : By number-of-turns adjustment, correspondence to products other than the above-mentioned characteristic is also possible, please consult.

● Bitiller winding. * ● Withstanding voltage : 100V DC for one minute between lines.


Shape and Dimensions





Recommended Land Pattern





Circuit Diagram



Impedance vs. Frequency






Precautions

Shelf Life

Use within 6 months. If the product is used after a storage period of 6 months or longer, confirm its solderability before use.

Recommended Soldering Conditions


- Soldering irons:
Tip temperature: $300 \pm 5^\circ\text{C}$
Duration of heat: approx. 4 seconds
- Flow soldering: not suitable
- Reflow soldering: Refer to the following temperature profile.



Tape and Reel Dimensions


SBS9080 (1000pcs./reel)

Dimensions of indented square-hole plastic tape



[mm]											
A ₀	B ₀	W	F	E	P ₁	P ₂	P ₀	D ₀	T ₁	T ₂	K
±0.3	±0.3	±0.3	±0.1	±0.1	±0.1	±0.1	±0.1	+0.1,-0	0.6≥	7.2≥	7.0≥
9.5	10.3	16	7.5	1.75	12	2.0	4.0	1.5	0.6	7.2	7.0


Reel dimensions



[mm]			
A	N	W ₁	W ₂
		±0.5	25≥
330	100	17.5	25


SBP-5001T (1000pcs./reel)

Dimensions of indented square-hole plastic tape



[mm]											
A	B	W	F	E	P ₁	P ₂	P ₀	D ₀	T ₁	T ₂	K
±0.3	±0.3	±0.3	±0.1	±0.1	±0.1	±0.1	±0.1	+0.1,-0	0.4≥	5.7≥	5.8≥
9.0	9.0	16	7.5	1.75	12	2.0	4.0	1.5	0.4	5.7	5.8


Reel dimensions



[mm]			
A	N	W ₁	W ₂
		+6,-0	25≥
330	79	16	25


M-521CT/M-522CT/M-523CT (conforms to EIAJ RC-1009) (1500pcs./reel)

Dimensions of indented square-hole plastic tape



[mm]											
A	B	W	F	E	P ₁	P ₂	P ₀	D ₀	T ₁	T ₂	K
±0.3	±0.3	±0.3	±0.1	±0.1	±0.1	±0.1	±0.1	+0.1,-0	max.	max.	max.
5.3	9.5	16	7.5	1.75	8.0	2.0	4.0	1.5	0.6	6.5	6.4


Reel dimensions



[mm]							
A	B	C	D	E	r	W ₁	W ₂
±3.0	±2.0	±0.2	±0.8	±0.5	—	max.	+6,-0
330	79	13	21	2.0	1.0	25	16

M-532CT (conforms to EIAJ RC-1009) (1000pcs./reel)

Dimensions of indented square-hole plastic tape




[mm]											
A	B	W	F	E	P ₁	P ₂	P ₀	D ₀	T ₁	T ₂	K
±0.3	±0.3	±0.3	±0.1	±0.1	±0.1	±0.1	±0.1	+0.1,-0	max.	max.	max.
7.9	9.4	16.0	7.5	1.75	12.0	2.0	4.0	1.5	0.6	6.9	6.8

Reel dimensions

[mm]							
A	B	C	D	E	r	W ₁	W ₂
±3.0	±2.0	±0.2	±0.8	±0.5	—	max.	+6,-0
330	80	13.0	21.0	2.0	1.0	25.0	16.0

M-538CT (conforms to EIAJ RC-1009) (1500pcs./reel)

Dimensions of indented square-hole plastic tape




[mm]											
A	B	W	F	E	P ₁	P ₂	P ₀	D ₀	T ₁	T ₂	K
±0.3	±0.3	±0.3	±0.1	±0.1	±0.1	±0.1	±0.1	+0.1,-0	max.	max.	max.
7.9	9.4	16.0	7.5	1.75	12.0	2.0	4.0	1.5	0.6	4.6	4.5

Reel dimensions

[mm]							
A	B	C	D	E	r	W ₁	W ₂
±3.0	±2.0	±0.2	±0.8	±0.5	—	max.	+6,-0
330	80	13.0	21.0	2.0	1.0	25.0	16.0

M-542CT (conforms to EIAJ RC-1009) (1000pcs./reel)

Dimensions of indented square-hole plastic tape




[mm]											
A	B	W	F	E	P ₁	P ₂	P ₀	D ₀	T ₁	T ₂	K
±0.3	±0.3	±0.3	±0.1	±0.1	±0.1	±0.1	±0.1	+0.1,-0	max.	max.	max.
9.5	10.5	16.0	7.5	1.75	12.0	2.0	4.0	1.5	0.6	7.2	7.0

Reel dimensions

[mm]							
A	B	C	D	E	r	W ₁	W ₂
±3.0	±2.0	±0.2	±0.8	±0.5	—	max.	+6,-0
330	100	13.0	21.0	2.0	1.0	25.0	17.5±0.5


M-608T/M-614T/M-620T (conforms to EIAJ RC-1009) (1500pcs./reel)

Dimensions of indented square-hole plastic tape



[mm]											
A	B	W	F	E	P ₁	P ₂	P ₀	D ₀	T ₁	T ₂	K
±0.3	±0.3	±0.3	±0.1	±0.1	±0.1	±0.1	±0.1	+0.1, -0	max.	max.	max.
6.4	10.2	16.0	7.5	1.75	8.0	2.0	4.0	1.5	0.6	6.5	6.4


Reel dimensions



[mm]							
A	B	C	D	E	r	W ₁	W ₂
±3.0	±2.0	±0.2	±0.8	±0.5	—	max.	+6, -0
330	79	13.0	21.0	2.0	1.0	25.0	16.0

DCM5/SCM5 Series (2000pcs /reel)

Dimensions of indented square-hole plastic tape



Model	A	B	C	D	E	F	G	H
SCM5 Series	16±0.3	8.0	6.3	8.3	7.5	1.75	5.2	0.38±0.05
DCM5 Series	24±0.3	20	14.5	17.2	11.5	1.75	6.8	0.38±0.05
DCM Series								

